

Performance & Strength

The enclosed body structure provides excellent protection for the main components while ensuring the comfort of maintenance.



Forks feature a unique structural design that allows for quick entry and exit from pallets. The leg plates are designed with an integrated stamping process, maximizing the strength of the forks.



Avant is equipped with a 24V DC permanent magnet motor and large-diameter drive wheel, offering strong obstacle-overcoming capabilities.



The classic enclosed box-type design ensures a more robust structure with higher waterproof and dustproof ratings.

High-strength frame design

High-strength and compact frame design ensures truck's robustness.


With a larger climbing angle, capable of reaching up to 6% even when fully loaded, the vehicle can be easily operated on leveling platforms and in various other delivery environments.

Green energy & Easy maintenance

Optional different Battery Capacities for applications

Avant comes standard with maintenance-free lithium iron phosphate batteries, equipped with an integrated BMS (Battery Management System) that ensures intelligent battery control and maximizes performance.

PWB-150



PWB-200



PWB-300



An external programming port makes parameter adjustments and overall vehicle maintenance more convenient and efficient.



The hydraulic system is highly integrated with the electrical system, facilitating easy installation and maintenance.





One-piece steel battery cover for perfect protection.



The steel battery cover can be easily opened allowing quick battery replacement.

Type sheet for industrial truck acc. to VDI 2198					No.20250412			
Identification								
1.2	Manufacturer's type designation		PWB-150		PWB-200		PWB-300	
1.3	Drive		Battery		Battery		Battery	
1.4	Operator type		Pedestrian		Pedestrian		Pedestrian	
1.5	Load Capacity / rated load	Q (t)	1.5		2.0		3.0	
1.6	Load centre distance	c (mm)	600		600		600	
1.8	Load distance ,centre of drive axle to fork	x (mm)	947		947		947	
1.9	Wheelbase	y (mm)	1189		1189		1189	
Weights								
2.1	Service weight	kg	121	130	123	133	180	185
2.2	Axle loading, laden front/rear	kg	520/1110	525/1115	525/1114	528/1120	952/2228	945/2240
2.3	Axle loading, unladen front/rear	kg	99/31	108/32	107/32	114/34	120/60	123/62
Wheels- Chassis								
3.1	Tires		PU		PU		PU	
3.2	Tire size,front	Øx w (mm)	Ø210×75		Ø210×75		Ø210×81.5	
3.3	Tire size,rear	Øx w (mm)	Ø 80×60 (80×83)		Ø 80×60 (80×83)		Ø 80×70 (80×93)	
3.4	Wheels,number front/rear(x-driven wheels)		1x/ 2(1x/ 4)		1x/ 2(1x/ 4)		1x/ 2(1x/ 4)	
3.7	Tread, rear	b11 (mm)	380	525	380	525	380	525
Basic Dimensions								
4.4	Lift	h3 (mm)	115		115		115	
4.9	Height of tiller in drive position min./ max.	h14 (mm)	630 / 1230		630 / 1230		630 / 1230	
4.15	Height, lowered	h13 (mm)	80		80		82±2	
4.19	Overall length	l1 (mm)	1530		1530		1530	
4.20	Length to face of forks	l2 (mm)	380		380		380	
4.21	Overall width	b1 (mm)	540	685	540	685	540	685
4.22	Fork dimensions	s/e/l (m m)	50 / 160 / 1150		50 / 160 / 1150		50 / 160 / 1150	
4.25	Width across forks	b5 (mm)	540	685	540	685	540	685
4.32	Ground clearance, centre of wheelbase	m2 (mm)	30		30		30	
4.34	Aisle width for pallets800X1200 lengthways(200mm safe distance)	Ast (mm)	2005		2005		2005	
4.35	Turning radius	Wa (mm)	1332		1332		1332	
Performance Data								
5.1	Travel speed, laden/ unladen	km/h	4.0/4.4		4.0/4.4		3.7/4.2	
5.2	Lift speed, laden/ unladen	m/s	0.016/0.021		0.015/0.020		0.01/0.014	
5.3	Lowering speed, laden/ unladen	m/s	0.005 / 0.026		0.05/0.024		0.05/0.026	
5.8	Max. gradeability, laden/ unladen	%	6/20		7/20		6/20	
5.10	Service brake		Electromagnetic		Electromagnetic		Electromagnetic	
E-Motor								
6.1	Drive motor rating S2 60min	kW	0.75		1.0		1.2	
6.2	Lift motor rating at S3 10%	kW	0.5		0.8		0.8	
6.3	Battery acc. to DIN 43531/ 35/ 36 A, B, C, no		No		No		No	
6.4	Battery voltage, nominal capacity K5	V / Ah	24/20(24/40; 24/60)		48 / 20		48 / 20 (48 / 30)	
6.5	Battery weight	kg	5.9		6		6	
6.6	Energy consumption acc. to VDI cycle	kWh/h	0.188		0.264		0.366	
Other Details								
8.1	Type of drive control		DC speed Control		DC speed Control		DC speed Control	
8.4	Sound level at driver's ear acc. to EN 12053	dB (A)	<70		<70		<70	



Official website



Our Wechat



NOBLELIFT CHINA

Address:528 Changzhou Road, Taihu Sub-district, Changxing, Zhejiang 313100 China
Tel:86-572-6210817 6210311
Fax:86-572-6210777 6128612
Email: info@noblelift.com
Http: www. noblelift. com www. noblelift. cn

NOBLELIFT NORTH AMERICA

Address:2461 S Wolf Road Des Plaines, IL 60018
Tel:001-847-595-7100
Fax:001-847-595-7200
Email: sales@nobleliftna.com
Http: www. nobleliftna. com

NOBLELIFT GERMANY

Werner-von-Siemens-Str. 12, 24568 Kaltenkirchen, Germany
Tel : +49 (0) 4191 - 9575603
Email: Mail@Noblelift-Germany.com
Http: www.Noblelift-Germany.com

NOBLELIFT RUSSIA

ООО «Ноблелифт Рус», 195067, Санкт-Петербург пр. Маршала Блюхера,д. 78, литер Б
Тел.: +7-800-700-28-97
Email: sales@noblelift.com.ru
Http: www.noblelift.com.ru

NOBLELIFT EUROPE

Registered Address:: 24 rue Lamartine, 38320 Eybens, France
Tel: +33 5 19 08 12 80
Email: support.eu@noblelift.com
Http: www.noblelift-eu.com

NOBLELIFT SOUTH EAST ASIA

No. 7, Jalan Astaka U8/84A, Seksyen U8, Bukit Jelutong, 40150 Shah Alam, Selangor Darul Ehsan, Malaysia.
Tel: +603 7831 8555
Email: sales@nobleliftsea.com
https: www.nobleliftsea.com

NOBLELIFT

www.noblelift.com

Avant

Lithium Powered Pallet Truck



NEW ARRIVAL



NOBLELIFT INTELLIGENT EQUIPMENT CO., LTD.

Brief Introduction of Avant


The inspiration for Avant comes from the PT16/20L series, which has a decade of successful market experience in heavy-duty models. It inherits the classic enclosed box-type design, featuring a more robust structure, higher waterproof and dustproof ratings, along with strong power. At the same time, it possesses the lightness and flexibility of a small material-handling vehicle, capable of efficiently working in various narrow spaces such as supermarkets, warehouses, logistics centers, sorting centers, truck compartments, containers, and freight elevators.



Delivery application

Optimized vehicle dimensions and self-weight make it convenient to use inside trucks and elevators, occupying less cargo weight and space.

(optional) 24V 8A truck charger available for charging between delivery operations.




Small turning radius



The vehicle is capable of making turns in confined spaces.

The compact vehicle body design, coupled with the upright walking function, is capable of handling work in narrow spaces such as truck compartments, containers, freight elevators, small warehouses, and supermarket aisles.

The handle is integrated with multiple functions, making operation convenient. It comes standard with a battery level display and fault indicator, allowing the truck condition to be easily assessed at a glance, enhancing truck management safety. All switches and buttons are ergonomically designed for easy operation.



Brake overriding mode

Press and hold the lowering button and the turtle-speed switch on the handle for 7 seconds, and the brake will be released. This allows you manually pull the truck for its relocation.

 The brake release is for forced relocation only and must not be used for regular operation.

